

PO Box 1461  
Salt Lake City, UT 84110



PH: 888-363-7740  
FAX: 801-363-6372

www.smartcrowdcontrol.com

## MB42x45 LCD



### Federally Accepted:

When you need a barricade to act as a perimeter or channelizer but want to save money, consider the MB42x45 LCD. It's federally accepted at 65 mph.

The MB42x45 fills the void between concrete barriers and drums. One person can easily set up in work zones.

### Features:

- Accepted by FHWA as Longitudinal Channelizing Device at TL3
- NCHRP-350 crash tested and accepted at TL3 (suitable for high speed work zones). Federal acceptance letter WZ-214.
- Barricades can hold battery-operated or solar safety lights.
- Triangular shape allows for easy storage by forming two barricades into a cube, which is then easily stackable.
- Requires no additional hardware or parts.
- Molded high density plastic expands if water freezes.



C01 light with adapter on MB42x45.

### Benefits:

- Forms interlocking wall with up to 15° radius.
- Due to their visibility and imposing nature, drivers respect these devices.
- Positive delineation. Widely spaced folding barricades, drums and cones are often confusing. The MB 42x45 provides visual delineation by forming a wall, thus greatly diminishing confusion for drivers and pedestrians.
- Barricades are safety stabilized when filled with water and stand up to bad weather or careless driving, clearly delineating work zones.
- The addition of lights and reflective sheeting make for a safe work zone at night.



MB42x45s can accommodate 28.5" x 36" signs or reflective panels. Signs are attached with screws into four pre-threaded holes. Lights attach easily.

### COLORS:

Orange, White

### COMPOSITION:

High impact UV resistant, high density polyethylene **FLASH**

### SIZE:

Height: 42" / 106.6 cm

Length: 45" / 114.3 cm

Width: 23.5" / 59.7 cm

### WEIGHT:

Empty: 44 lbs. / 19.9 kg

Full: 760 lbs. / 344.7 kg

### WATER BALLAST:

18.8 gallons / 71.1 liters

### Certifications:

- Meets MUTCD specification 6F.66 for Longitudinal Channelizing Devices.
- Meets NCHRP-350 requirements for Longitudinal Channelizing Devices at TL3.
- Accepted by FHWA as a Longitudinal Channelizing Device for speeds of up to 62.5 mph (TL3).

Accept no imitations.

